

<b>KKM ab</b>	Three-phase hermetically sealed oil-immersed shunt reactor 30-148kVAr, 20.5kV, YN	<b>SHR 8-20,5 2,5-12,5A</b>
---------------	--	-----------------------------

### TECHNICAL DATA

1.	Manufacturer		KKMPower d.o.o, Serbia				
2.	Reactor type		Oil-immersed, hermetically sealed				
3.	Reactor kind		Shunt reactor. A bank of three separate single-phase reactor, mounted in the same tank and coupled in YN vector group, able to sustain earth-fault.				
4.	Standard		IEC 60076-6 (Clause 7)				
5.	Reactor name		SHR 8-20,5 2,5-12,5				
6.	Number of phases		3				
7.	Rated frequency	[Hz]	50				
8.	Highest voltage of equipment	[kV]	24				
9.	Insulation level	[kV]	LI 125/AC 50				
10.	Rated voltage	[kV]	20.5				
11.	Winding connection		YN				
	Tap position		1	2	3	4	5
12.	Rated power	[kVAr]	30	59	89	118	148
13.	Rated current	[A]	0.833	1.67	2.5	3.33	4.17
14.	Zero-sequence impedance	[Ω/phase]	14176	7088	4735	3555	2852
15.	Rated fault current in neutral	[A]	2.5	5	7.5	10	12.5
16.	Fault duration	[h]	2				
17.	Winding material	Cu/Al	Copper				
18.	Tap changer	Yes/No	Yes, with five taps				
19.	Total losses at 75°C	[W]	2520(maximum, at tap 5 active)				
20.	R/X ratio at 75°C	[%]	<1.25(for each tap)				
21.	Sound power level	[dB(A)]	<61				
22.	Type of cooling		ONAN				
23.	Installation altitude	[m]	<1000				
24.	Maximum temperature of ambient	[°C]	40				
25.	Maximum temperature rise of winding	[K]	65				
26.	Maximum temperature rise of oil	[K]	60				
27.	Thermal class of insulation		A				
28.	Installation conditions		Outdoor				
29.	Approximate length of reactor	[mm]	885				

<b>KKM ab</b>		Three-phase hermetically sealed oil-immersed shunt reactor 30-148kVAr, 20.5kV, YN		<b>SHR 8-20,5 2,5-12,5A</b>
30.	Approximate width of reactor	[mm]	905	
31.	Approximate height of reactor	[mm]	1300	
32.	Mass of oil in reactor	[kg]	235	
33.	Total mass of reactor	[kg]	1190	

Date: 05.04.2017

Made by: D.Kovinić

KKM - Peter Fälldin - KKM AB - 10/19/2017 8:52:45 PM - 83.255.108.210