

<b>KKM ab</b>	Three-phase oil-immersed shunt reactor with conservator	Offer No. <b>P16-127</b>
	3000(2000)kVAr, 20.5kV, Y	Drawing No. <b>MS-1629</b>
		Version <b>4.0</b>
		Page <b>1 of 2</b>

## TECHNICAL DATA

1.	Manufacturer		KKMPower d.o.o, Serbia
2.	Reactor type		Oil-immersed, with conservator
3.	Reactor kind		Shunt reactor, for compensation
4.	Standard		IEC 60076-6 (Clause 7)
5.	Reactor name		SSHR2 3000-20.5
6.	Rated power	[kVAr]	3000(2000)
7.	Number of phases		3
8.	Rated frequency	[Hz]	50
9.	Highest voltage of equipement	[kV]	24
10.	Insulation level	[kV]	LI 125/AC 50
11.	Rated voltage	[kV]	20.5
12.	Winding connection		Y
13.	Rated current	[A]	84.49(56.33)
14.	Winding material	Cu/Al	Copper
15.	Tap changer	Yes/No	No. With two sets of terminal.
16.	Total losses at 75°C	[W]	21000(13500)
17.	Type of cooling		ONAN
18.	Sound power level	[dB(A)]	<83
19.	Instalation altitude	[m]	<1000
20.	Maximum temperature of ambient	[°C]	40
21.	Maximum temperature rise of winding	[K]	65
22.	Maximum temperature rise of oil	[K]	60
23.	Thermal class of insulation		A
24.	Instalation conditions		Outdoor
25.	Approximate length of reactor	[mm]	2000
26.	Approximate width of reactor	[mm]	1200
27.	Approximate height of reactor	[mm]	2500
28.	Mass of oil in reactor	[kg]	800
29.	Total mass of reactor	[kg]	5100